Printing date 04/09/2018

Reviewed on 04/03/2018

# **1** Identification

- · Product identifier
- Trade name: <u>Hi-Tech ProMender Flex "A"</u>
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Progressive Fastening Systems Inc. Hi-Tech Systems 1190 N. Del Rio Place Ontario, CA 91764

Phone (909) 945-5530 Fax (909) 945-3009 www.hitechpolyurea.com

· Information department: Product Safety Department

· Emergency telephone number:

INFOTRAC (24 HOURS) USA 1-800-535-5053 / INTERNATIONAL 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS ( OR DANGEROUS GOODS) INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

#### 2 Hazard(s) identification

· Classification of the substance or mixture

GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

# GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

• *Hazard-determining components of labeling:* diphenylmethanediisocyanate, isomeres and homologues 4,4'-methylenediphenyl diisocyanate methylenediphenyl diisocyanate

• Hazard statements Harmful if inhaled. Causes skin irritation.

(Contd. on page 2)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

(Contd. of page	:1)
Causes serious eye irritation.	
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause an allergic skin reaction.	
Suspected of causing cancer.	
May cause respiratory irritation.	
May cause damage to organs through prolonged or repeated exposure.	
· Precautionary statements	
<i>Obtain special instructions before use.</i>	
Do not handle until all safety precautions have been read and understood.	
Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling	
Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
[In case of inadequate ventilation] wear respiratory protection.	
If on skin: Wash with plenty of water.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to a	lo
Continue rinsing.	.0.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
If experiencing respiratory symptoms: Call a poison center/doctor.	
Wash contaminated clothing before reuse.	
Store in a well-ventilated place. Keep container tightly closed.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = 1	
$\frac{2}{10} Reactivity = 0$	
· HMIS-ratings (scale 0 - 4)	
FIRE 1 Fire = 1	
<b>REACTIVITY</b> $\bigcirc$ <i>Reactivity</i> = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• <b>PBT</b> : Not applicable.	
• <b>vPvB:</b> Not applicable.	
3 Composition/information on ingredients	

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

\*

• **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

	(C	ontd. of page 2)
· Dangerous	components:	
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	>25-≤50%
101-68-8	4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;    Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	>10-≤25%
	methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;    Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	>2.5-<5%

#### **4** First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for 15 minutes under running water. If symptoms persist, consult a doctor. • After swallowing:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if victim is unconscious or having convulsions. If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam • Special hazards arising from the substance or mixture
- Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

- · Advice for firefighters
- · Protective equipment:

*Firefighters should be equippped with self-contained breathing apparatus and turn-out gear* • *Additional information* 

• Additional information  $D^{\circ}$ 

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.*
- Clear area. Ensure adequate ventilation. Wear suitable personal protective cloining and en
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: For small amounts: Absorb isocyanate with suitable absorbant material(see 40 CFR sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a

(Contd. on page 4)

Printing date 04/09/2018

Reviewed on 04/03/2018

#### Trade name: Hi-Tech ProMender Flex "A"

(Contd.	of	page	3)

well-ventila	ted area (outside). Spill area can be decontaminated with the folowing recommended dec	conta. of page 3)
	xture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio.	Alow to stand
	18 hours to allow escape of evolved carbon dioxide.	
	mounts: If temporary control of isocyanate vapor is required, a blanket of protein f	
	m may be placed over the spill. Transfer as much liquid as possible via pump or vacuu not sealed containers for disposal. For residues: The following measures should be to	
	ash down spill area with decontamination solution. Allow solution to stand for at leas	
Dike spillag		i 10 minutes.
1 0	he collected material according to regulations.	
	taminated material as waste according to item 13.	
	uate ventilation.	
	o other sections	
	7 for information on safe handling.	
	8 for information on personal protection equipment.	
	13 for disposal information.	
	ction Criteria for Chemicals	
· PAC-1:		
	diphenylmethanediisocyanate, isomeres and homologues	0.15 mg/m <sup>3</sup>
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m <sup>3</sup>
26447-40-5	methylenediphenyl diisocyanate	29 mg/m <sup>3</sup>
· PAC-2:		
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3.6 mg/m <sup>3</sup>
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m <sup>3</sup>
26447-40-5	methylenediphenyl diisocyanate	40 mg/m <sup>3</sup>
· PAC-3:		
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	22 mg/m <sup>3</sup>
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m <sup>3</sup>
26447-40-5	methylenediphenyl diisocyanate	240 mg/m <sup>3</sup>

#### 7 Handling and storage

· Handling:

#### · Precautions for safe handling

Ensure thorough ventilation of stores and work area. Protect against moisture.

Ensure good ventilation/exhaustion at the workplace. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of busting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

• Information about protection against explosions and fires: No special measures required.

• Conditions for safe storage, including any incompatibilities Segregate from foods and animal feeds. Segregate friom acids and bases. • Storage:

• Requirements to be met by storerooms and receptacles:

Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) Storage temperature 27-35° C

(Contd. on page 5)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

(Contd. of page 4)

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m<sup>3</sup>, 0.02 ppm

- REL Long-term value: 0.05 mg/m<sup>3</sup>, 0.005 ppm Ceiling limit value: 0.2\* mg/m<sup>3</sup>, 0.02\* ppm \*10-min
- TLV Long-term value: 0.051 mg/m<sup>3</sup>, 0.005 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

#### • Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:

Wear face shield if splashing hazard exists.



Tightly sealed goggles

· Body protection: Protective work clothing

(Contd. on page 6)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

(Contd. of page 5)

Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Dark brown	
Odor:	musty, slight odour	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	200 °C (392 °F)	
Flash point:	198 °C (388.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	400 °C (752 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.14195 g/cm³ (9.52957 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with Water:	Not missible on difficult to min	
Partition coefficient (n-octanol/wat	Not miscible or difficult to mix.	
	er); Noi delermined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gl	
Solids content:	100.0 %	
Other information	No further relevant information available.	

# **10 Stability and reactivity**

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)

US ·

Printing date 04/09/2018

Reviewed on 04/03/2018

#### Trade name: Hi-Tech ProMender Flex "A"

(Contd. of page 6)

Possibility of hazardous reactions
Reacts with alcohols, amines, aqueous acids and alkalis.
Danger of polymerization.
Exothermic reaction.
Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.
Exothermic reaction. Reacts with strong acids and alkalies. Reacts with oxidizing agents.

· Conditions to avoid Avoid moisture

• Incompatible materials:

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

• Hazardous decomposition products:

aromatic isocyanates, gases/vapours

carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

#### **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

*Oral LD50 9,592 mg/kg (mouse)* 

Inhalative LC50/4 h 15 mg/l

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

*Oral LD50 2,200 mg/kg (mouse)* 

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

- on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

#### · Carcinogenic categories

· IARC (Int	ernational Agency for Research on Cancer)	
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
101-68-8	4,4'-methylenediphenyl diisocyanate	3
$\cdot NTP$ (Nat	ional Toxicology Program)	
None of th	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	

None of the ingredients is listed.

#### **12 Ecological information**

· Toxicity

• Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

(Contd. on page 8)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADN, IMDG, IATA	not regulated	
	noi regulatea	
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, ĬMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

\*

# **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

<sup>-</sup> US

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

	(Contd. of page
Section 313 (Specific toxic chemical listings):	
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	
101-68-8 4,4'-methylenediphenyl diisocyanate	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	CBD
101-68-8 4,4'-methylenediphenyl diisocyanate	D, CB
TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
GHS label elements The product is classified and labeled according to the Globally Hazard pictograms	Harmonized System (GHS).
GHS07 GHS08	

· Signal word Danger

· Hazard-determining components of labeling: diphenylmethanediisocyanate, isomeres and homologues 4,4'-methylenediphenyl diisocyanate methylenediphenyl diisocyanate · Hazard statements Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

(Contd. on page 10)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

(Contd. of page 9)
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If on skin: Wash with plenty of water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- · Contact: Safety Department
- Date of preparation / last revision 04/09/2018 / 2

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity - Category 2

(Contd. on page 11)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "A"

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 • \* Data compared to the previous version altered. (Contd. of page 10)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

#### **1** Identification

- · Product identifier
- Trade name: <u>Hi-Tech ProMender Flex ''B''</u>
- · Details of the supplier of the safety data sheet

 Manufacturer/Supplier: Progressive Fastening Systems Inc. Hi-Tech Systems 1190 N. Del Rio Place Ontario, CA 91764

Phone (909) 945-5530 Fax (909) 945-3009 www.hitechpolyurea.com

· Information department: Product Safety Department

· Emergency telephone number:

INFOTRAC (24 HOURS) USA 1-800-535-5053 / INTERNATIONAL 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS ( OR DANGEROUS GOODS) INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

#### 2 Hazard(s) identification

· Classification of the substance or mixture

GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Flam. Liq. 4 H227 Combustible liquid.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger


Hazard-determining components of labeling: Distillates (petroleum), hydrotreated light Solvent naphta (petroleum) heavy aliph.
Hazard statements Combustible liquid.
Causes serious eye irritation. May be fatal if swallowed and enters airways.
Precautionary statements Keep away from flames and hot surfaces. – No smoking. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor.

(Contd. on page 2)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "B"



# **3** Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	•	
64742-47-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226; I Asp. Tox. 1, H304	>10-≤25%
64742-96-7	Solvent naphta (petroleum) heavy aliph.	>10-≤25%
	🚸 Asp. Tox. 1, H304	
	calcium oxide	≥1-≤2.5%
	 Eye Dam. 1, H318	

# 4 First-aid measures

· Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for 15 minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink 200-300ml of water
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "B"

(Contd. of page 2)

#### **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam
- Special hazards arising from the substance or mixture Hazards during fire-fighting:
- nitrous gases, fumes/smoke, isocyanate, vapour
- Advice for firefighters
   Protective equipment: Firefighters should be equipped with self-contained breathing apparatus and turn out gear.
- Additional information Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up: Dispose of the collected material according to regulations. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.*
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

102-60-3 1,1',1'''-ethylenedinitrilotetrapropan-2-ol	34 mg/m <sup>3</sup>
1305-78-8 calcium oxide	6 mg/m <sup>3</sup>
PAC-2:	
102-60-3 1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	370 mg/m <sup>3</sup>
1305-78-8 calcium oxide	110 mg/m <sup>3</sup>
· PAC-3:	
102-60-3 1,1',1"',1"''-ethylenedinitrilotetrapropan-2-ol	2,200 mg/m <sup>3</sup>
1305-78-8 calcium oxide	660 mg/m <sup>3</sup>

#### 7 Handling and storage

· Handling:

- · Precautions for safe handling Ensure thorough ventilation of stores and work area. Protect against moisture.
- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- Segregate from foods and animal feeds. Segregate friom acids and bases.
- Storage:
- Requirements to be met by storerooms and receptacles:
- Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "B"

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

1305-78-8 calcium oxide

PEL Long-term value: 5 mg/m<sup>3</sup>

REL Long-term value: 2 mg/m<sup>3</sup>

TLV Long-term value: 2 mg/m<sup>3</sup>

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment: Not required.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  **Material of gloves** 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

# 9 Physical and chemical properties • Information on basic physical and chemical properties • General Information • Appearance: Form: Liquid Color: Clear to slight Cloudy • Odor: slight odour

(Contd. of page 3)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "B"

	(Contd. of	page
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	200 °C (392 °F)	
Flash point:	61 °C (141.8 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	210 °C (410 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	0.5 Vol %	
Upper:	6.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	2 hPa (1.5 mm Hg)	
• Density at 20 °C (68 °F):	0.99576 g/cm³ (8.30962 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
• Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00~%	
	0.0 g/l / 0.00 lb/gl	
Solids content:	78.9 %	
• Other information	No further relevant information available.	

# **10 Stability and reactivity**

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Exothermic reaction. Reacts with strong acids and alkalies. Reacts with oxidizing agents.

• *Conditions to avoid Temperature < 0 degrees Celsius* 

Avoid moisture

(Contd. on page 6)

US

Printing date 04/09/2018

Reviewed on 04/03/2018

#### Trade name: Hi-Tech ProMender Flex "B"

(Contd. of page 5)

• Incompatible materials: acids, oxidizing agents, isocyanates acids, amings, alcohols, water, Alkalines

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

• Hazardous decomposition products: aromatic isocyanates, gases/vapours

carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

# **11 Toxicological information**

· Information on toxicological effects

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- $\cdot$  Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- $\cdot$  **Other adverse effects** No further relevant information available.

# **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "B"

(Contd. of page 6) Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

· Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

# 14 Transport information

· UN-Number · DOT, ADN, IMDG, IATA	not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated	
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA · Class	not regulated	
· Packing group · DOT, IMDG, IATA	not regulated	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		
· UN "Model Regulation":	not regulated	

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 8)

JS -

Printing date 04/09/2018

Reviewed on 04/03/2018

Trade name: Hi-Tech ProMender Flex "B"

(Contd. of page 7)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

• *Hazard-determining components of labeling: Distillates (petroleum), hydrotreated light Solvent naphta (petroleum) heavy aliph.* 

· Hazard statements

Combustible liquid. Causes serious eye irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Safety Department

· Date of preparation / last revision 04/09/2018 / 2

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 9)

<sup>•</sup> US

Printing date 04/09/2018

Reviewed on 04/03/2018

#### Trade name: Hi-Tech ProMender Flex "B"

	(Contd. of page 8)
EINECS: European Inventory of Existing Commercial Chemical Substances	(1.0.1)
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Liq. 4: Flammable liquids – Category 4	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
Asp. Tox. 1: Aspiration hazard – Category 1	
• * Data compared to the previous version altered.	