Printing date 04/09/2018

Reviewed on 03/30/2018

1 Identification

- · Product identifier
- Trade name: Hi Tech Spall TX3 "A"
- Details of the supplier of the safety data sheet Progressive Fastening Systems Inc. Hi-Tech Systems 1190 N. Del Rio Place Ontario, CA 91764

· Information department: Product Safety Department

Phone: (909) 945-5530 Fax: (909) 945-3009 www.hitechpolyurea.com

INFOTRAC (24 HOURS) USA 1-800-535-5053 / INTERNATIONAL 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS (OR DANGEROUS GOODS) INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

2 *Hazard*(*s*) *identification*

· Emergency telephone number:

· Classification of the substance or mixture

GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- Carc. 2 H351 Suspected of causing cancer.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Causes serious eye irritation.

Hazard-determining components of labeling: 4,4'-methylenediphenyl diisocyanate diphenylmethanediisocyanate,isomeres and homologues methylenediphenyl diisocyanate
Hazard statements Harmful if inhaled. Causes skin irritation.

(Contd. on page 2)

US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

	(Contd. of page 1)
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause an allergic skin reaction.	
Suspected of causing cancer.	
May cause respiratory irritation.	
May cause damage to organs through prolonged or repeated exposure.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
[In case of inadequate ventilation] wear respiratory protection.	
If on skin: Wash with plenty of water.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if preser	nt and easy to do.
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
If experiencing respiratory symptoms: Call a poison center/doctor.	
Wash contaminated clothing before reuse.	
Store in a well-ventilated place. Keep container tightly closed.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	ons.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = 1	
2 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{\text{HEALTH}} = *2$	
FIRE 1 $Fire = 1$	
REACTIVITY Reactivity = 0	
• Other hazards	
• Results of PBT and vPvB assessment	
• PBT: Not applicable. • vPvB: Not applicable.	
3 Composition/information on ingredients	

· Chemical characterization: Mixtures

*

• **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

⁻ US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

	(C	ontd. of page 2)
· Dangerous co	omponents:	
101-68-8 4	4,4'-methylenediphenyl diisocyanate	>25-≤50%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; (1) Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
9016-87-9 a 4 1	diphenylmethanediisocyanate,isomeres and homologues 🗞 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; 🚯 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	>25-≤50%
26447-40-5 m 4 1	nethylenediphenyl diisocyanate � Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; 아 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	>2.5-<5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for 15 minutes under running water. If symptoms persist, consult a doctor. • After swallowing:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if victim is unconscious or having convulsions. If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam • Special hazards arising from the substance or mixture
- Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

- · Advice for firefighters
- · Protective equipment:

Firefighters should be equippped with self-contained breathing apparatus and turn-out gear

• Additional information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.*
- Environmental precautions: No special measures required.
- *Methods and material for containment and cleaning up:* Dispose of the collected material according to regulations.

(Contd. on page 4)

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

Dispose con	taminated material as waste according to item 13.	(Contd. of page 3)
-	<i>quate ventilation.</i>	
	o other sections	
•	7 for information on safe handling.	
	8 for information on personal protection equipment.	
	13 for disposal information.	
• Protective A	ction Criteria for Chemicals	
· PAC-1:		
101-68-8	4,4'-methylenediphenyl diisocyanate	$0.45 mg/m^3$
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	0.15 mg/m ³
26447-40-5	methylenediphenyl diisocyanate	29 mg/m ³
· PAC-2:		
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3.6 mg/m ³
26447-40-5	methylenediphenyl diisocyanate	40 mg/m ³
· PAC-3:		
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	22 mg/m ³
26447-40-5	methylenediphenyl diisocyanate	240 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure thorough ventilation of stores and work area. Protect against moisture.

Ensure good ventilation/exhaustion at the workplace. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of busting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

• Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate friom acids and bases. • Storage:

• Requirements to be met by storerooms and receptacles:

Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

US

Printing date 04/09/2018


Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

(Contd. of page 4)

US

	ponents with limit values that require monitoring at the workplace: 68-8 4,4'-methylenediphenyl diisocyanate
	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
	Long-term value: 0.2* mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m ³ , 0.005 ppm
Addi	tional information: The lists that were valid during the creation were used as basis.
Perso Gene Keep Imme Wash Store Avoid Brea In ca respi	osure controls onal protective equipment: eral protective and hygienic measures: o away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work. e protective clothing separately. d contact with the eyes and skin. thing equipment: use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us fratory protective device that is independent of circulating air. ection of hands:
	Protective gloves
Due	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the preparation/ th nical mixture.
	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation prial of gloves
varie the g	selection of the suitable gloves does not only depend on the material, but also on further marks of quality and as from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of love material can not be calculated in advance and has therefore to be checked prior to the application. Atration time of glove material
The e	exact break through time has to be found out by the manufacturer of the protective gloves and has to b
	Tightly sealed goggles
Dodu	protection: Protective work clothing



Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

		(Contd. of page
Color:	Dark brown	
· Odor:	musty , slight odour	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	200 °C (392 °F)	
· Flash point:	198 °C (388.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	400 °C (752 °F)	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
• Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
• Density at 20 °C (68 °F):	1.15153 g/cm ³ (9.60952 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gl	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Exothermic reaction. Reacts with strong acids and alkalies. Reacts with oxidizing agents.

- · Conditions to avoid Avoid moisture
- · Incompatible materials:

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

(Contd. on page 7)

[·] Chemical stability

____US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

(Contd. of page 6)

\cdot Hazardous decomposition products:

aromatic isocyanates, gases/vapours carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 4,796 mg/kg (mouse)

Inhalative LC50/4 h 11.4 mg/l

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

 · IARC (International Agency for Research on Cancer)

 101-68-8
 4,4'-methylenediphenyl diisocyanate

 9016-87-9
 diphenylmethanediisocyanate,isomeres and homologues
 3

 · NTP (National Toxicology Program)
 3

 None of the ingredients is listed.
 • OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

(Contd. of page 7)

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA · Class	not regulated
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
• Transport in bulk according to Annex II oj MARPOL73/78 and the IBC Code	r Not applicable.
· UN ''Model Regulation'':	not regulated

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)

[•] US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

	(Contd. of page
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
101-68-8 4,4'-methylenediphenyl diisocyanate	D, CBD
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	CBD
TLV (Threshold Limit Value established by ACGIH) None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.	
GHS label elements The product is classified and labeled according to the Globally Harn	
GHS07 GHS08	
• Signal word Danger	
Hazard-determining components of labeling:	
4,4'-methylenediphenyl diisocyanate	
diphenylmethanediisocyanate, isomeres and homologues	
methylenediphenyl diisocyanate	
· Hazard statements	
Harmful if inhaled.	
Causes shin imitation	
Causes skin irritation.	
Causes serious eye irritation.	
Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.	
Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer.	

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 10)

US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi Tech Spall TX3 "A"

(Contd. of page 9)

IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Safety Department
- · Date of preparation / last revision 04/09/2018 / 4
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 • * Data compared to the previous version altered.

Printing date 04/09/2018

Reviewed on 03/30/2018

1 Identification

- · Product identifier
- Trade name: <u>Hi-Tech Spall TX3 ''B''</u>
- Details of the supplier of the safety data sheet Progressive Fastening Systems Inc. Hi-Tech Systems 1190 N. Del Rio Place Ontario, CA 91764

· Information department: Product Safety Department

Phone: (909) 945-5530 Fax: (909) 945-3009 www.hitechpolyurea.com

INFOTRAC (24 HOURS) USA 1-800-535-5053 / INTERNATIONAL 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS (OR DANGEROUS GOODS) INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

2 *Hazard*(*s*) *identification*

· Emergency telephone number:

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements
- Combustible liquid.
- · Precautionary statements
- Keep away from flames and hot surfaces. No smoking.
- Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH	0	Health = 0
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity =

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

0

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 2)

US

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi-Tech Spall TX3 "B"

	(Contd. of page 1)
· Dangerous		
64742-47-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226;	≥10-≤25%
	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304	
64742-96-7	Solvent naphta (petroleum) heavy aliph.	≥10-≤25%
	🗞 Asp. Tox. 1, H304	

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for at least 15 minutes under running water.
- After swallowing:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if victim is unconscious or having convulsions. If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam
- Special hazards arising from the substance or mixture Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

- · Advice for firefighters
- · Protective equipment:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

· Additional information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Dispose of the collected material according to regulations. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
102-60-3	1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	34 mg/m ³
1305-78-8	calcium oxide	6 mg/m ³
		(Contd. on page 3
	1	(Contd. on p

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi-Tech Spall TX3 "B"

		(Contd. of page 2)
· PAC-2:		
102-60-3	1,1',1"',1"''-ethylenedinitrilotetrapropan-2-ol	370 mg/m ³
1305-78-8	calcium oxide	110 mg/m ³
• PAC-3:		
102-60-3	1,1',1",1"'-ethylenedinitrilotetrapropan-2-ol	$2,200 mg/m^3$
1305-78-8	calcium oxide	660 mg/m ³

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure thorough ventilation of stores and work area. Protect against moisture.
- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- Segregate from foods and animal feeds. Segregate friom acids and bases.

· Storage:

- Requirements to be met by storerooms and receptacles:
- Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling.

(Contd. on page 4)

US –

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/09/2018

*

Reviewed on 03/30/2018

Trade name: Hi-Tech Spall TX3 "B"

· Body protection: Protective work clothing

Physical and chemical proper	ties	
Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Amber colored	
Odor:	slight odour	
Odor threshold:	Not determined.	
<i>pH-value at 20 °C (68 °F):</i>	7	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	200 °C (392 °F)	
Flash point:	>61 °C (>141.8 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	250 °C (482 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	2 hPa (1.5 mm Hg)	
Density at 20 °C (68 °F):	0.99576 g/cm³ (8.30962 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	400 mPas	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gl	
Solids content:	85.0 %	
Other information	No further relevant information available.	

(Contd. on page 5)

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi-Tech Spall TX3 "B"

(Contd. of page 4)

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Exothermic reaction. Reacts with strong acids and alkalies. Reacts with oxidizing agents.

- · Conditions to avoid Avoid moisture
- Incompatible materials:

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

- · Hazardous decomposition products:
- aromatic isocyanates, gases/vapours

carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- \cdot on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • Results of PBT and vPvB assessment

- *PBT:* Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi-Tech Spall TX3 "B"

(Contd. of page 5)

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADN, IMDG, IATA	not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated	
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA · Class	not regulated	
· Packing group · DOT, IMDG, IATA	not regulated	
· Environmental hazards:	Not applicable.	
 Special precautions for user Stowage Category 	Not applicable. A	
· Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 7)

US

Printing date 04/09/2018

Reviewed on 03/30/2018

(Contd. of page 6)

Trade name: Hi-Tech Spall TX3 "B"

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms** Void

· Signal word Warning

· Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

[·] Contact: Safety Department

[•] Date of preparation / last revision 04/09/2018 / 2

[·] Abbreviations and acronyms:

TLV: Threshold Limit Value

Printing date 04/09/2018

Reviewed on 03/30/2018

Trade name: Hi-Tech Spall TX3 "B"

Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4 Asp. Tox. 1: Aspiration hazard – Category 1 • *** Data compared to the previous version altered.** (Contd. of page 7)

US