Printing date 04/09/2018 Reviewed on 04/03/2018

1 Identification

· Product identifier

· Trade name: Hi-Tech Spall TX Gel "A"

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Progressive Fastening Systems Inc.

Hi-Tech Systems 1190 N. Del Rio Place Ontario, CA 91764 Phone (909) 945-5530 Fax (909) 945-3009 www.hitechpolyurea.com

- · Information department: Product Safety Department
- · Emergency telephone number:

INFOTRAC~(24~HOURS)~USA~1-800-535-5053~/~INTERNATIONAL~1-352-323-3500~USE~ONLY~FOR~HAZARDOUS~MATERIALS~(~OR~DANGEROUS~GOODS)~INCIDENT~-~SPILLS,~LEAKS,~FIRE,~EXPOSURE,~OR~ACCIDENT~CN109479

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate diphenylmethanediisocyanate,isomeres and homologues methylenediphenyl diisocyanate

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

(Contd. on page 2)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 1)

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2Fire = 1REACTIVITY $\boxed{0}$ Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

		ontd. of page 2)
· Dangerous o	components:	
101-68-8	4,4'-methylenediphenyl diisocyanate	>25-≤50%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	>25-≤50%
	& Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; � Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
26447-40-5	methylenediphenyl diisocyanate	>2.5-<5%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for 15 minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if victim is unconscious or having convulsions. If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam
- · Special hazards arising from the substance or mixture

Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

- · Advice for firefighters
- · Protective equipment:

Firefighters should be equippped with self-contained breathing apparatus and turn-out gear

· Additional information Keep containers cool by spraying with water if exposed to fire.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

For small amounts: Absorb isocyanate with suitable absorbant material (see 40 CFR sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination

(Contd. on page 4)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 3)

solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio. Alow to stand for at least 48 hours to allow escape of evolved carbon dioxide.

For large amounts: If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal. For residues: The following measures should be taken for final cleanup: Wash down spill area with decontamination solution. Allow solution to stand for at least 10 minutes. Dike spillage.

Dispose of the collected material according to regulations.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· Protective	Action Criteria for Chemicals	
· PAC-1:		
101-68-	8 4,4'-methylenediphenyl diisocyanate	0.45 mg/m ³
9016-87-	diphenylmethanediisocyanate,isomeres and homologues	0.15 mg/m ³
26447-40	5 methylenediphenyl diisocyanate	29 mg/m³
· PAC-2:		
101-68-	8 4,4'-methylenediphenyl diisocyanate	5 mg/m³
9016-87-	diphenylmethanediisocyanate,isomeres and homologues	3.6 mg/m ³
26447-40	5 methylenediphenyl diisocyanate	40 mg/m³
· PAC-3:		
101-68-	8 4,4'-methylenediphenyl diisocyanate	55 mg/m³
9016-87-	diphenylmethanediisocyanate,isomeres and homologues	22 mg/m³
26447-40	5 methylenediphenyl diisocyanate	240 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure thorough ventilation of stores and work area. Protect against moisture.

Ensure good ventilation/exhaustion at the workplace. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of busting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids and bases.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use(s) No further relevant information available.*

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

REL Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm

*10-min

TLV Long-term value: 0.051 mg/m³, 0.005 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbant and particulate filter can be used as long as appropriate precautions and change out schedules are in place. For emergency or non-routine, high exposure situations, including confined space entry use a NIOSH- certified full facepiece pressure demand self contained breathing apparatus (SCBA) or full facepiece pressure demand supplied air respirator (SAR) with escape provisions.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Suitable materials may include Chloroprene rubber (Neoprene), nitrile rubber (Buna N), chlorinated polyethylene, polyvinylchloride (Pylox), butyl rubber, depending upon conditions of use.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

· Eye protection:

Wear face shield if splashing hazard exists.



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: Dark brown · Odor: musty, slight odour · Odor threshold: Not determined. · pH-value: Not determined. · Change in condition Undetermined. Melting point/Melting range: 200 °C (392 °F) Boiling point/Boiling range: 199 °C (390.2 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. 400 °C (752 °F) · Ignition temperature: · Decomposition temperature: Not determined. Product is not selfigniting. · Auto igniting: · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Lower: Not determined. Upper: Not determined. · Vapor pressure: Not determined. Not determined. · Density: · Relative density Not determined. · Vapor density Not determined. Not determined. · Evaporation rate · Solubility in / Miscibility with Water: Not miscible or difficult to mix. $\cdot \textit{Partition coefficient (n-octanol/water):} \ \textit{Not determined}.$ · Viscosity: Dynamic at 20 °C (68 °F): 100 mPas Kinematic: Not determined. · Solvent content: **VOC** content: 0.00 % 0.0 g/l / 0.00 lb/gl

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 6)

Solids content: 100.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Exothermic polymerization.

Reacts with alcohols, amines, aqueous acids and alkalis.

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Exothermic reaction. Reacts with strong acids and alkalies. Reacts with oxidizing agents.

- · Conditions to avoid Avoid moisture
- · Incompatible materials:

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

· Hazardous decomposition products:

aromatic isocyanates, gases/vapours

carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classific
--

ATE	(Acute	Toxicity	Estimate)
-----	--------	----------	-----------

 Oral
 LD50
 4,796 mg/kg (mouse)

 Inhalative
 LC50/4 h
 11.4 mg/l

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International	Agency for	Research on	Cancer)

mine (me	rational rightly for Research on Cancer)	
101-68-8	4,4'-methylenediphenyl diisocyanate	3
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	3

(Contd. on page 8)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 7)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name		
DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	

(Contd. on page 9)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 8)

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)			
	101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
	9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	CBD

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:
- 4,4'-methylenediphenyl diisocyanate

(Contd. on page 10)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 9)

diphenylmethanediisocyanate,isomeres and homologues

methylenediphenyl diisocyanate

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Safety Department
- · Date of preparation / last revision 04/09/2018 / 1
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Printing date 04/09/2018 Reviewed on 04/03/2018

Trade name: Hi-Tech Spall TX Gel "A"

(Contd. of page 10)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.

IIC -

Printing date 04/09/2018 Reviewed on 04/05/2018

1 Identification

· Product identifier

· Trade name: Hi-Tech Spall TX Gel "B"

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Progressive Fastening Systems Inc.

Hi-Tech Systems 1190 N. Del Rio Place Ontario, CA 91764 Phone (909) 945-5530 Fax (909) 945-3009 www.hitechpolyurea.com

- · Information department: Product Safety Department
- · Emergency telephone number:

INFOTRAC (24 HOURS) USA 1-800-535-5053 / INTERNATIONAL 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS (OR DANGEROUS GOODS) INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

5 GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenebis(cyclohexylamine)

Solvent naphta (petroleum) heavy aliph.

diethylmethylbenzenediamine

Distillates (petroleum), hydrotreated light

(Contd. on page 2)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 1)

· Hazard statements

Combustible liquid.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Get medical advice/attention if you feel unwell.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3Fire = 2

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

64742-96-7 Solvent naphta (petroleum) heavy aliph.

>10-≤25%

♦ Asp. Tox. 1, H304

(Contd. on page 3)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

		Contd. of page 2)
64742-47-8	Distillates (petroleum), hydrotreated light	>10-≤25%
	🚸 Flam. Liq. 3, H226; \delta Asp. Tox. 1, H304	
	diethylmethylbenzenediamine	>2.5-<10%
	🕸 STOT RE 2, H373; 🕂 Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2A, H319	
1761-71-3	4,4'-methylenebis(cyclohexylamine)	≥3-<5%
	♦ Acute Tox. 3, H301; ♦ Skin Corr. 1B, H314; Eye Dam. 1, H318	

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam
- · Special hazards arising from the substance or mixture

Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

- · Advice for firefighters
- · Protective equipment:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

· Additional information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose of the collected material according to regulations.

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· Froiective Action Crueria for Chemicais	
· PAC-1:	
102-60-3 1,1',1"'-ethylenedinitrilotetrapropan-2-ol	34 mg/m ³
· PAC-2:	
102-60-3 1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	370 mg/m³
· PAC-3:	
102-60-3 1,1',1"',1"''-ethylenedinitrilotetrapropan-2-ol	$2,200 \text{ mg/m}^3$

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure thorough ventilation of stores and work area. Protect against moisture.
- Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids and bases.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

61 °C (141.8 °F)

Product is not selfigniting.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· General Information	
· Appearance:	
Form:	Liquid
Color:	Amber colored
· Odor:	slight odour
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	200 °C (392 °F)

· Information on basic physical and chemical properties

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	210 °C (410 °F)

· Decomposition temperature:	Not determined.

· Auto igniting:

· Flash point:

Lower:	0.5 Vol %
Upper:	6.5 Vol %

· Vapor pressure at 20 °C (68 °F): 2 hPa (1.5 mm Hg)

(Contd. on page 6)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

		(Contd. of page
· Density:	Not determined.	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	tter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gl	
Solids content:	86.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Exothermic reaction. Reacts with strong acids and alkalies. Reacts with oxidizing agents.

· Conditions to avoid

Temperature < 0 degrees Celsius

Avoid moisture

· Incompatible materials:

acids, oxidizing agents, isocyanates

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

· Hazardous decomposition products:

aromatic isocyanates, gases/vapours

carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
ATE (A	cute To	oxicity Estimate)
Oral	LD50	1,937 mg/kg
Dermal	LD50	>44,000 mg/kg (rat)

68479-9	8-1 die	thylmethylbenzenediamine
Oral	LD50	738 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

(Contd. on page 7)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 6)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $The \ product \ shows \ the \ following \ dangers \ according \ to \ internally \ approved \ calculation \ methods \ for \ preparations:$

Harmful

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

HIS

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 7)

Transport information	
UN-Number DOT IMDG, IATA	not regulated UN3082
· UN proper shipping name · DOT	not regulated
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (diethylmethylbenzenediamine), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (diethylmethylbenzenediamine)
· Transport hazard class(es)	N.O.S. (aleinyimeinyivenzeneaiamine)
· DOT · Class	not regulated
· IMDG, IATA	O Miscellangous dangarous substances and articles
· Class · Label	9 Miscellaneous dangerous substances and articles 9
Packing group DOT IMDG, IATA	not regulated III
· Environmental hazards: · Marine pollutant: · Special marking (IATA):	Product contains environmentally hazardous substance. diethylmethylbenzenediamine Symbol (fish and tree) Symbol (fish and tree)
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE. LIQUID, N.O.S. (DIETHYLMETHYLBENZENEDIAMINE), 9, III

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenebis(cyclohexylamine)

Solvent naphta (petroleum) heavy aliph.

diethylmethylbenzenediamine

Distillates (petroleum), hydrotreated light

· Hazard statements

Combustible liquid.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

(Contd. on page 10)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 9)

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Get medical advice/attention if you feel unwell.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Safety Department
- · Date of preparation / last revision 04/09/2018 / 6
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

(Contd. on page 11)

Printing date 04/09/2018 Reviewed on 04/05/2018

Trade name: Hi-Tech Spall TX Gel "B"

(Contd. of page 10)

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 * Data compared to the previous version altered.